


- ① FINISHED GRADE.
- ② PLANT MATERIAL.
- ③ CLEAN SOIL, AMENDED/NATIVE - FREE OF ROCK AND DEBRIS.
- ④ POP-UP SPRAY SPRINKLER BODY, 1/2" INLET, SEE LEGEND FOR TYPE, SEE SPRINKLER DETAIL FOR INFORMATION.
- ⑤ **STREET ELBOW 90°- 1/2", LASCO 'POLY',** (MIPT x FIPT), PART # M412-005.
- ⑥ **ELBOW 90°- 1/2", LASCO BLUE TWISTER,** (Barb x MIPT), PART # 3300-005, (2) REQ'D.
- ⑦ FUNNY PIPE, SEE LEGEND FOR MFG, WITH 12" LAY LENGTH MINIMUM.
- ⑧ TEE OR ELBOW, LASCO SCH40, SIZE PER LATERAL LINE PIPE x 1/2" FIPT.

NOTE: SEE LASCO SWIVEL JOINTS FOR OVER 4 G.P.M. HEADS

INSTALL POPUP SPRAY SPRINKLER 4" FROM PAVED EDGE, BUILDINGS AND FENCE AREAS, INSTALL PLUMB AND FLUSH TO GRADE, ADJUST COVERAGE TO AVOID OVERSPRAY ONTO PAVED SURFACES, FENCES, BUILDINGS AND PARKING LOTS.



LASCO BLUE TWISTER FITTINGS, SWING RISER

N.T.S. - APPLICABLE TO SPRINKLER HEADS UNDER 4 G.P.M.

DETAIL-FILE